

## **【CLAIMS】**

### **【Claim 1】**

A drum type washing machine comprising:

- 5 a cabinet forming an exterior of the drum type washing machine;  
a tub provided within the cabinet;  
a damper having one end connected to the tub and the other end rotatably connected to the cabinet;  
a damper pin having predetermined elasticity and rotatably joining the damper to the  
10 cabinet; and,  
an elastic member provided within the damper pin.

### **【Claim 2】**

- The drum type washing machine of claim 1, wherein the elastic member comprises a  
15 rubber having a predetermined elasticity.

### **【Claim 3】**

- The drum type washing machine of claim 1, wherein the elastic member comprises a  
spring having a predetermined elasticity.

20

### **【Claim 4】**

The drum type washing machine of claim 1, wherein a slot is formed along a lateral side of the damper pin.

### **【Claim 5】**

The drum type washing machine of claim 1, wherein a hanging sill is provided to one

side of the damper pin and a hanging piece is provided to the other side of the damper pin to prevent the damper pin from being separated.

**【Claim 6】**

- 5 The drum type washing machine of claim 5, wherein the hanging piece is formed as one body with the damper pin.

**【Claim 7】**

- 10 The drum type washing machine of claim 6, wherein the hanging piece has a predetermined elasticity.

**【Claim 8】**

- A drum type washing machine comprising:  
a cabinet forming an exterior of the drum type washing machine;  
15 a tub provided within the cabinet;  
a damper having one end connected to the tub and the other end rotatably connected to the cabinet;  
a damper pin rotatably joining the damper to the cabinet to have a slot along a lateral side of the damper pin; and  
20 a felter provided within the damper pin.

**【Claim 9】**

- The drum type washing machine of claim 8, wherein the felter is impregnated with a lubricant.  
25

**【Claim 10】**

The drum type washing machine of claim 9, wherein the lubricant is an oil.

**【Claim 11】**

The drum type washing machine of claim 9, wherein the lubricant is a grease.

5

**【Claim 12】**

The drum type washing machine of claim 8, wherein the slot is formed along a lateral side of the damper pin.

10 **【Claim 13】**

The drum type washing machine of claim 8, wherein a hanging sill is provided to one side of the damper pin and a hanging piece is provided to the other side of the damper pin to prevent the damper pin from being separated.

15 **【Claim 14】**

The drum type washing machine of claim 13, wherein the hanging piece is formed as one body with the damper pin.

**【Claim 15】**

20 The drum type washing machine of claim 13, wherein the hanging piece has a predetermined elasticity.